

**Cement Head
Circulating Head
Circulating Swage**

Shandong Saigao Group Corporation

Add: No 12111,Jingshi Road, Lixia District, Jinan City, Shandong . P.R. China

TEL: +86-531-69959201 FAX: +86-531-69959201 www.saigaogroup.com

E-mail: sales@saigaogroup.com WeChat:18653457231 QQ 2889690629

1. Single Plug Cement Head

- Compact structure, reasonable design and structure are made of high strength alloy steel AISI4135H, high pressure.
- The bottom of the single plug cement head has a union type of quick-latch Joint for easy and casing to connect.
- Plug Dropping Indicator is used to indicate the whereabouts through the cement head into the casing.
- Cement head cap and the body connecting thread, as well as quick-latch joint pitch trapezoidal screw thread are large, easy quick installation.
- Internal balance cement head: Body I.D. greater than cementing plug diameter, the internal pressure balance can be achieved.



Product No.DSC-01



Product No.DSC-02

Standard configuration No.DSC-01:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Quick-Latch Joint.
- Manifold, Downward union.
- Integral Plug Valve.
- The type cement heads are available in sizes 4" through 20".

Single Plug Cement Head No.DSC-02:

- Plug Dropping Indicator.
- Double Plug release Plunger Assembly.
- Without Quick-Latch Joint.
- Manifold, Downward union.
- Integral Plug Valve.
- The type cement heads are available in sizes 16" through 20".





Product No.DSC-03

Product No.DSC-04

Single Plug Cement Head No.DSC-03:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Quick-Latch Joint.
- Integral Plug Valve.
- Integral manifold by tee and cross, no thread connection.
- The type cement heads are available in sizes 4" through 20".

Single Plug Cement Head No.DSC-04:

- Plug Dropping Indicator.
- Double Plug release Plunger Assembly.
- Without Quick-Latch Joint.
- Integral Plug Valve.
- Integral manifold by tee and cross, no thread connection.
- The type cement heads are available in sizes 16" through 20".



Product No.DSC-05



Product No.DSC-06

Single Plug Cement Head No.DSC-05:

- Simple cement head.
- Plug Dropping Indicator.
- Double Plug release Plunger Assembly.
- No manifold.
- On the cover of a union.
- The type cement heads are available in sizes 4" through 20".

Single Plug Cement Head No.DSC-06:

- Plug Dropping Indicator.
- Release Plunger Assembly.
- Quick-Latch Joint. Rotate 60 °
- Integral Manifold.
- Integral Plug Valve.
- The type cement heads are available in sizes 4" through 20".



Product No.DSC-07



Product No.DSC-08

Single Plug Cement Head No.DSC-07:

- Plug Dropping Indicator.
- Plug Release Plunger Assembly.
- Integral Plug Valve.
- Thread connection manifold, union port level.
- The type cement heads are available in sizes 4" through 13³/₈".

Single Plug Cement Head No.DSC-08:

- Simple cement head.
- No manifold.
- Plug Dropping Indicator.
- Release Plunger Assembly.
- Quick-Latch Joint.
- The type cement heads are available in sizes 4" through 13³/₈".



Product No.DSC-09



Product No.DSC-10

Single Plug Cement Head No.DSC-09:

- Plug Dropping Indicator.
- Double Plug release Plunger Assembly.
- Plug valves threaded connection
- Manifold, Downward union.
- Quick-Latch Joint.
- The type cement heads are available in sizes 4" through 13³/₈".

Single Plug Cement Head No.DSC-10:

- Plug Dropping Indicator.
- Release Plunger Assembly.
- Manifold, Downward union.
- Plug valves threaded connection
- The type cement heads are available in sizes 16" through 20".



Product No.DSC-11



Product No.DSC-12

Single Plug Cement Head No.DSC-11:

- Simple cement head.
- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Plug valves threaded connection
- Manifold, Downward union.
- The type cement heads are available in sizes 4" through 13³/₈".

Single Plug Cement Head No.DSC-12:

- Release Plunger Assembly.
- Complex manifold.
- Integral Plug Valve.
- Pressure gauges, flow meter.
- The type cement heads are available in sizes 4" through 20".

Single Plug Cement Head Main Technical Parameters

Specifications, mm	Working Pressure, MPa	I.D. of Plug Container, mm	Length of Plug Container, mm
4" (Φ101.6mm)	35, 50, 70	Φ102	425
4½" (Φ114.3mm)	35, 50, 70	Φ115	425
5" (Φ127mm)	35, 50, 70	Φ127	425
5½" (Φ139.7mm)	35, 50, 70	Φ140	425
5¾" (Φ146mm)	35, 50, 70	Φ146	425
6⅝" (Φ168.27mm)	35, 50, 70	Φ168	425
7" (Φ177.8mm)	35, 50, 70	Φ178	425
7⅝" (Φ193.67mm)	35, 50, 70	Φ194	425
7¾" (Φ196.85mm)	35, 50, 70	Φ197	425
7⅞" (Φ200.03mm)	35, 50, 70	Φ200	425
8⅝" (Φ219.1mm)	35, 50, 70	Φ219	425
9⅝" (Φ244.5mm)	35, 50, 70	Φ245	425
9⅞" (Φ250.83mm)	35, 50, 70	Φ250	425
10¾" (Φ273mm)	35, 50, 70	Φ273	425
11¾" (Φ298.45mm)	21, 35, 50	Φ298	425
12¾" (Φ324mm)	21, 35, 50	Φ324	425
13⅜" (Φ339.7mm)	21, 35, 50	Φ340	425
13⅝" (Φ346.08mm)	21, 35, 50	Φ346	425
16" (Φ406.4mm)	21, 35	Φ406	600
16¾" (Φ426mm)	21, 35	Φ426	600
18⅝" (Φ473.1mm)	21, 35	Φ473	600
20" (Φ508mm)	21, 35	Φ508	600

- API: LTC、STC、BTC.
- GOST: OTTM.
- Premium connections: Tenaris hydril, JFE, TPCQ, WSP, VAM, HUNTING, Bao Steel.

2. Double Plug Cement Head

- Compact structure, reasonable design and structure are made of high strength alloy steel, high pressure.
- The bottom of the double plug cement head has a union type of quick-latch Joint for easy and casing to connect.
- Indicator is used to indicate the whereabouts through the cement head into the casing.
- Cement head cap and the body connecting thread, as well as quick-latch joint pitch trapezoidal screw thread are large, easy quick installation.
- Internal balance cement head: Body I.D. greater than cementing plug diameter, the internal pressure balance can be achieved.



Product No.SSC-01



Product No.SSC-02

Standard configuration No.SSC-01:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Quick-Latch Joint.
- Manifold, Downward union.
- Integral Plug Valve.
- The type cement heads are available in sizes 4" through 20".

Double Plug Cement Head No.SSC-02:

- Plug Dropping Indicator.
- Double Plug release Plunger Assembly.
- Quick-Latch Joint, Rotate 60 °
- Manifold, Downward union.
- Plug valves threaded connection.
- The type cement heads are available in sizes 16" through 20".



Product No.SSC-03



Product No.SSC-04

Double Plug Cement Head No.SSC-03:

- Plug Dropping Indicator.
- Double Plug Release Plunger Assembly.
- Quick-Latch Joint.
- Manifold, Downward union.
- Plug valves threaded connection.
- The type cement heads are available in sizes 4" through 13³/₈".

Double Plug Cement Head No.SSC-04:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Quick-Latch Joint.
- Manifold.
- Plug valves threaded connection.
- The type cement heads are available in sizes 4" through 13³/₈".

Double Plug Cement Head Main Technical Parameters

Specifications mm	Working Pressure, MPa	I.D. of Plug Container mm	Length of Plug Container, mm	
			Conventional Cementing	Stage Collar
4" (Φ101.6mm)	35, 50, 70	Φ102	425	425
4½" (Φ114.3mm)	35, 50, 70	Φ115	425	425
5" (Φ127mm)	35, 50, 70	Φ127	425	425
5½" (Φ139.7mm)	35, 50, 70	Φ140	425	425
5¾" (Φ146mm)	35, 50, 70	Φ146	425	425
6⅝" (Φ168.27mm)	35, 50, 70	Φ168	425	425
7" (Φ177.8mm)	35, 50, 70	Φ178	425	425
7⅝" (Φ193.67mm)	35, 50, 70	Φ194	425	425
7¾"(Φ196.85mm)	35, 50, 70	Φ197	425	425
7⅞"(Φ200.03mm)	35, 50, 70	Φ200	425	425
8⅝" (Φ219.1mm)	35, 50, 70	Φ219	425	550
9⅝" (Φ244.5mm)	35, 50, 70	Φ245	425	550
9⅞" (Φ250.83mm)	35, 50, 70	Φ250	425	550
10¾" (Φ273mm)	35, 50, 70	Φ273	425	550
11¾" (Φ298.45mm)	21, 35, 50	Φ298	425	550
12¾" (Φ324mm)	21, 35, 50	Φ324	425	600
13⅜" (Φ339.7mm)	21, 35, 50	Φ340	425	600
13⅝" (Φ346.08mm)	21, 35, 50	Φ346	425	600
16" (Φ406.4mm)	21, 35	Φ406	600	650
16¾" (Φ426mm)	21, 35	Φ426	600	650
18⅝" (Φ473.1mm)	21, 35	Φ473	600	650
20" (Φ508mm)	21, 35	Φ508	600	650

- API: LTC、STC、BTC.
- GOST: OTTM.
- Premium connections: Tenaris hydril, JFE, TPCQ, WSP, VAM, HUNTING, Bao Steel.

3. Drill Pipe Single Plug Cement Head

- Special tool for pumping slurry and releasing plug. The ZSC Drill Pipe Single Plug Cement Head can be connected with Drill pipe.
- Compact structure, reasonable design and structure are made of high strength alloy steel, high pressure.
- Indicator is used to indicate the whereabouts through the cement head into the casing.



Product No.ZSC-01



Product No.ZSC-02

Drill Pipe Cement Head No.ZSC-01:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Manifold, Downward union.
- Plug valves threaded connection.
- The type cement heads are available in sizes 2 $\frac{7}{8}$ " through 5 $\frac{1}{2}$ ".

Drill Pipe Cement Head No.ZSC-02:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Pitching device.
- Manifold.
- Plug valves threaded connection.
- The type cement heads are available in sizes 2 $\frac{7}{8}$ " through 5 $\frac{1}{2}$ ".



Product No.ZSC-03



Product No.ZSC-04

Rotary Drill Pipe Cement Head No.ZSC-03:

- Plug Dropping Indicator.
- Plug release Plunger Assembly.
- Pitching device.
- Bearing, rotating easy.
- Manifold.
- Plug valves threaded connection.
- The type cement heads are available in sizes 2 $\frac{7}{8}$ " through 5 $\frac{1}{2}$ ".

Drill Pipe Cement Head No.ZSC-04:

- Simple cement head.
- Plug release Plunger Assembly.
- No manifold.
- No plug valves.
- The type cement heads are available in sizes 2 $\frac{7}{8}$ " through 5 $\frac{1}{2}$ ".



Drill Pipe Cement Head No.ZSC-05:

- Plug release Plunger Assembly.
- Manifold.
- Plug valves threaded connection.
- The type cement heads are available in sizes 2⁷/₈" through 5¹/₂".

Product No.ZSC-05

Drill Pipe Cement Head Main Technical Parameters

Specifications mm	Working-Pressure MPa	I.D. of Plug Container mm	Length of Plug Container, mm	Connection Threads
----------------------	-------------------------	---------------------------------	---------------------------------	--------------------

2 7/8" (Φ73mm)	50, 70	Φ55	425	2 7/8" IF (NC31)
3 1/2" (Φ89mm)	50, 70	Φ72	425	3 1/2" IF (NC38)
4" (Φ101.6mm)	50, 70	Φ90	425	3 1/2" IF (NC38)
4 1/2" (Φ114.3mm)	50, 70	Φ101	425	4" IF (NC46)
5" (Φ127mm)	50, 70	Φ102	425	4 1/2" IF (NC50)
5 1/2" (Φ139.7mm)	50, 70	Φ115	425	FH5 1/2

3. Circulating Head

The top of circulating head connects to the kelly, the bottom connects to the casing. It is used to circulate the cement slurry before cementing. Sometimes the cementing head can be replaced by lifting circulation head.

Features

- Its upper end is drill pipe box, the nether end is casing pin. It is a crossover(X/O) with hollow inside.
- Main body are made from AISI4145H alloy steel.



Product No.CH-01

Circulating Head Main Technical Parameters

Size (in)	Body OD Size(mm)	ID size (mm)	Top box conn	Bottom Pin Conn	Length (mm)	W.P. psi
4"	121	70	3 1/2" IF	4" Casing thread	600 / 915	10000
4 1/2"	121	70	3 1/2" IF	4 1/2" Casing thread		
5"	128	70	3 1/2" IF	5" Casing thread		
5 1/2"	145	70	3 1/2" IF	5 1/2" Casing thread		
5 3/4"	148	70	3 1/2" IF	5 3/4" Casing thread		
6 5/8"	178	100	4 1/2" IF	6 5/8" Casing thread		
7"	179	100	4 1/2" IF	7" Casing thread		
7 5/8"	195	100	4 1/2" IF	7 5/8" Casing thread		
7 3/4"	198	100	4 1/2" IF	7 3/4" Casing thread		
7 7/8"	202	100	4 1/2" IF	7 7/8" Casing thread		
8 5/8"	222	100	4 1/2" IF	8 5/8" Casing thread		
9 5/8"	270	100	4 1/2" IF	9 5/8" Casing thread		
9 7/8"	270	100	4 1/2" IF	9 7/8" Casing thread		

10 ³ / ₄ "	275	100	4 ¹ / ₂ " IF	10 ³ / ₄ " Casing thread		
11 ³ / ₄ "	300	100	4 ¹ / ₂ " IF	11 ³ / ₄ " Casing thread		
12 ³ / ₄ "	326	100	4 ¹ / ₂ " IF	12 ³ / ₄ " Casing thread		
13 ³ / ₈ "	342	100	4 ¹ / ₂ " IF	13 ³ / ₈ " Casing thread		
13 ⁵ / ₈ "	348	100	4 ¹ / ₂ " IF	13 ⁵ / ₈ " Casing thread		
16"	410	100	4 ¹ / ₂ " IF	16" Casing thread		
16 ³ / ₄ "	428	100	4 ¹ / ₂ " IF	16 ³ / ₄ " Casing thread		
18 ⁵ / ₈ "	475	100	4 ¹ / ₂ " IF	18 ⁵ / ₈ " Casing thread		
20"	510	100	4 ¹ / ₂ " IF	20" Casing thread		

4. Circulating Swage

- The top of Circulating Swage connects to the hoses, the bottom connects to the casing.
- Main body is made from AISI4145H alloy steel.



Product No.CS-01



Product No.CS-02



Circulating Swage Main Technical Parameters

Size (in)	Body OD Size(mm)	ID size (mm)	Top box conn	Bottom Pin Conn	Length (mm)	W.P. psi
4"	121	50.8	2" FIG1502F	4" Casing thread	500	10000
4 ¹ / ₂ "	121	50.8	2" FIG1502F	4 ¹ / ₂ " Casing thread		
5"	128	50.8	2" FIG1502F	5" Casing thread		
5 ¹ / ₂ "	145	50.8	2" FIG1502F	5 ¹ / ₂ " Casing thread		
5 ³ / ₄ "	148	50.8	2" FIG1502F	5 ³ / ₄ " Casing thread		
6 ⁵ / ₈ "	178	50.8	2" FIG1502F	6 ⁵ / ₈ " Casing thread		
7"	179	50.8	2" FIG1502F	7" Casing thread		
7 ⁵ / ₈ "	195	50.8	2" FIG1502F	7 ⁵ / ₈ " Casing thread		
7 ³ / ₄ "	198	50.8	2" FIG1502F	7 ³ / ₄ " Casing thread		
7 ⁷ / ₈ "	202	50.8	2" FIG1502F	7 ⁷ / ₈ " Casing thread		
8 ⁵ / ₈ "	222	50.8	2" FIG1502F	8 ⁵ / ₈ " Casing thread		
9 ⁵ / ₈ "	270	50.8	2" FIG1502F	9 ⁵ / ₈ " Casing thread		
9 ⁷ / ₈ "	270	50.8	2" FIG1502F	9 ⁷ / ₈ " Casing thread		

10 ³ / ₄ "	275	50.8	2" FIG1502F	10 ³ / ₄ " Casing thread		
11 ³ / ₄ "	300	50.8	2" FIG1502F	11 ³ / ₄ " Casing thread		
12 ³ / ₄ "	326	50.8	2" FIG1502F	12 ³ / ₄ " Casing thread		
13 ³ / ₈ "	342	50.8	2" FIG1502F	13 ³ / ₈ " Casing thread		
13 ⁵ / ₈ "	348	50.8	2" FIG1502F	13 ⁵ / ₈ " Casing thread		
16"	410	50.8	2" FIG1502F	16" Casing thread		
16 ³ / ₄ "	428	50.8	2" FIG1502F	16 ³ / ₄ " Casing thread		
18 ⁵ / ₈ "	475	50.8	2" FIG1502F	18 ⁵ / ₈ " Casing thread		
20"	510	50.8	2" FIG1502F	20" Casing thread		

5. Drill Pipe Circulating Swage

- The top of Drill Pipe Circulating Swage connects to the hoses, the bottom connects to the Drill Pipe.
- Main body are made from AISI4145H alloy steel.



Product No.DCS-01

Drill Pipe Circulating Swage Main Technical Parameters

Size (in)	Body OD Size(mm)	ID size (mm)	Top box conn	Bottom Pin Conn	Length (mm)	W.P. psi
2 ⁷ / ₈ "	105	50.8	2" FIG1502F	2 ⁷ / ₈ "IF (NC31)	305	10000
3 ¹ / ₂ "	121	50.8	2" FIG1502F	3 ¹ / ₂ "IF (NC38)		
4"	146	50.8	2" FIG1502F	3 ¹ / ₂ "IF (NC38)		
4 ¹ / ₂ "	158	50.8	2" FIG1502F	4"IF (NC46)		
5"	158	50.8	2" FIG1502F	4 ¹ / ₂ "IF (NC50)		
5 ¹ / ₂ "	185	50.8	2" FIG1502F	FH5 ¹ / ₂		

6. Quick-Latch Circulating Swage

- The top of Quick-Latch Circulating Swage connects to the hoses,



the bottom connects to the cement head female sub.

- Main body are made from AISI4135H alloy steel.



Product No.QCS-01

7. Rotary Circulating Swage

- The top of Rotary Circulating Swage connects to the drill pipe or the hose, the bottom connects to the Drill Pipe.
- Main body is made from AISI4145H alloy steel.
- Ball bearing, rotating easy.
- Working pressure 5000psi



Product No.RCS-01



Product No.RCS-02

8. Cement Head Accessory



Product No.Part-01

Chrome-plated Pins



Product No.Part-02

Pin Assembly



Product No.Part-03

Plug Valves Threaded Connection



Product No.Part-04

Integral Plug Valve





Product No.Part-05
Landing Female Joint



Product No.Part-06
Pressure Gauge Joint



Product No.Part-08
Sealing

Product No.Part-07
Pressure Gauge

9. Technical Requirements and Testing

Cement head /Circulating Head/Swage body, quick-latch joints, cap, pin assembly and other materials mechanical properties must meet the following requirements:

- Yield strength: $\sigma_s \geq 550\text{Mpa}$
- Tensile strength: $\sigma_b \geq 750\text{MPa}$
- Toughness: $A_{kv} \geq 60\text{J}$
- Heat Treatment Hardness: HB270 ~ 300
- Seals should be acid, alkali, oil.
- Seals Shore A hardness: HS 60~80
- Temperature: $-30\text{ }^\circ\text{C} \sim 120\text{ }^\circ\text{C}$

Cement Head /Circulation Head/Swage Pressure Testing

Working Pressure Psi	Testing Pressure Psi	First Time Steady Pressure minutes	Second Time Steady Pressure minutes
2000	3000	3	15
3000	4500	3	15
5000	7500	3	15
7150	10000	3	15

Plug Valve and Manifold Pressure Testing

Working Pressure Psi	Testing Pressure Psi	First Time Steady Pressure minutes	Second Time Steady Pressure minutes
10000	10000	3	15
15000	15000	3	15